



Mr. Koni Nishiura
NGK SPARK PLUG CO., LTD.
Q58486

APPENDIX

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE CLAIMS:

The claims are amended as follows:

1. (Five times amended) A printed wiring substrate having a planar surface and a built-in capacitor on which an IC chip is mounted, said printed wiring substrate comprising a capacitor accommodation cavity selected from the group consisting of a closed-bottom cavity and a through hole cavity extending in the thickness direction of the printed wiring substrate and a capacitor disposed in said cavity, wherein the capacitor and the printed wiring substrate are fixed together with an insulating resin filling a gap between the cavity and the capacitor, characterized in that:

the capacitor comprises:

a pair of electrodes or electrode groups; and

the capacitor comprises a plurality of capacitor terminals, wherein the respective capacitor terminals are electrically connected to one or the other of the paired electrodes or electrode groups;

the printed wiring substrate comprises a plurality of substrate terminals;



Mr. Koni Nishiura
NGK SPARK PLUG CO., LTD.
Q58486

the IC chip comprises a plurality of connection-to-capacitor terminals and a plurality of connection-to-substrate terminals;

the plurality of capacitor terminals of the capacitor are respectively flip-chip-bonded directly to a plurality of connection-to-capacitor terminals of the IC chip; and

the plurality of substrate terminals of the printed wiring substrate are respectively flip-chip-bonded to a plurality of connection-to-substrate terminals of the IC chip.

2. (Five times amended) A printed wiring substrate having a planar surface and a built-in capacitor on which an IC-chip-carrying printed wiring substrate is mounted, said printed wiring substrate comprising a capacitor accommodation cavity selected from the group consisting of a closed-bottom cavity and a through hole cavity extending in the thickness direction of the printed wiring substrate and a capacitor disposed in said cavity, wherein the capacitor and the printed wiring substrate are fixed together with an insulating resin filling a gap between the cavity and the capacitor, characterized in that:

the capacitor comprises:

a pair of electrodes or electrode groups; and

the capacitor comprises a plurality of capacitor terminals, wherein the respective capacitor terminals are electrically connected to one or the other of the paired electrodes or electrode groups;



Mr. Koni Nishiura
NGK SPARK PLUG CO., LTD.
Q58486

the printed wiring substrate comprises a plurality of substrate terminals;

the IC chip-carrying printed wiring circuit comprises a plurality of connection-to-capacitor terminals and a plurality of connection-to-substrate terminals;

the plurality of capacitor terminals of the capacitor are respectively bonded in a connection-face-to-connection-face manner directly to a plurality of connection-to-capacitor terminals of the IC-chip-carrying printed wiring substrate; and

the plurality of substrate terminals of the printed wiring substrate are respectively bonded in a connection-face-to-connection-face manner to a plurality of connection-to-substrate terminals of the IC-chip-carrying printed wiring substrate.

4. (Four times amended) A printed wiring substrate having [a] planar surface and a built-in capacitor for mounting an IC chip or IC-chip-carrying printed wiring substrate having a plurality of connection-to-capacitor terminals and a plurality of connection-to-substrate terminals, said printed wiring substrate comprising a capacitor accommodation cavity selected from the group consisting of a closed-bottom cavity and a through hole cavity extending in the thickness direction of the printed wiring substrate and a capacitor disposed in said cavity, wherein the capacitor and the printed wiring substrate are fixed together with an insulating resin filling a gap between the cavity and the capacitor, characterized in that:

the capacitor comprises:

a pair of electrodes or electrode groups; and



Mr. Koni Nishiura
NGK SPARK PLUG CO., LTD.
Q58486

the capacitor comprises a plurality of capacitor terminals capable of being respectively flip-chip-bonded or bonded in a connection-face-to-connection-face manner to a plurality of connection-to-capacitor terminals of the IC chip or IC-chip-carrying printed wiring substrate, wherein the respective capacitor terminals are electrically connected to one or the other of the paired electrodes or electrode group; and

the printed wiring substrate comprises a plurality of substrate terminals capable of being respectively flip-chip-bonded or bonded in a connection-face-to-connection-face manner directly to a plurality of connection-to-substrate terminals of the IC chip or IC-chip-carrying printed wiring substrate.